

TECHNICAL SPECIFICATION

TDS 3SP20

Ver. B/03.21

TOP FLOOR PAINT

Top Floor Paint is a solvent-based floor paint formulated with acrylic resins. It is specially developed for use on paved floors, parking spaces and terrains paved with tarmac or concrete. It has excellent adhesion, resistance to wearing and high temperature fluctuations. It also maintains its elasticity even in extremely low temperatures. It has very good workability and fast drying, providing satin finish.

APPLICATION

- *Substrate Preparation*
Surfaces should be clean, dry and free from unsound materials, dust, oils, etc. After the substrate has been prepared, apply one coat of **Top Floor Paint diluted up to 10%. Apply the second layer diluted up to 5%**. Take care to apply it in temperatures between 10-30 °C and low relative humidity (<75%). For old or unsound surfaces from concrete, prime with the solvent-based impregnation primer **Isacryl** before application.
- *Application*
The product is applied with a brush, roller or spray gun. Dilute with Thinner A up to 5-10% for application with a brush or roller and 10% for application with a spray gun.
- *Spreading rate*
7-9 m²/lt on properly prepared surfaces.
- *Drying time*
Dust dry after 10-15 minutes, touch dry after ½ hour and complete hardening in 2-3 hours. Drying time depends highly on weather conditions (temperature, humidity).
- *Cleaning of tools*
Try to remove as much paint as possible from the tools before cleaning them. Clean tools immediately after use with Thinner A or Thinner Ducco For General Use.
- *Restrictions*
Do not apply the product when the ambient temperature and/or the substrate temperature is lower than 5°C.

PACKAGING

Available in metal pails of 0.75lt, 2.5lt and 10lt.



STORAGE

Store in a dry and cool place (5°C to 35°C). Keep container tightly closed.

SAFE USE

Avoid contact with eyes. Consult the product's SDS for more information.

TECHNICAL CHARACTERISTICS

- *Binder:* Modified acrylic resin.
- *Drying:*
 - Surface drying: 30min
 - Through drying: 2hrs min
 - Full drying: 6hrs
- *Repainting:* Minimum after 12hrs.
- *Viscosity:* 2500 – 3000 cp (spindle No5, 20 rpm, 25°C).
- *Density:* 1,58-1,60 gr/ml.
- *Thinning:* 5-10% with White Spirit.
- *Colors:* Available in White, Grey (RAL 7040) and all RAL color shades after special order.
- *Finis:* Satin.

VOLATILE ORGANIC COMPOUNDS

EU limit value for this product (cat A/i): 500 gr/lit. This product contains maximum 500 gr/lit VOC.

DRAPA
chemie

DRAPA CHEMIE - DRAKOPOYLOS S.A.
Megaridos Ave & Chiou Str, Mavri Yiora Area,
19300, Aspropyrgos, Attiki, Greece
tel: +302105570191, fax: +302105593945
Email: drapa1@otenet.gr, Url: www.drapa.gr
EN ISO 9001:2015, Cert. Nr. 123045
EN ISO 14001:2015, Cert. Nr. GR/002/2015-3

