

## TECHNICAL SPECIFICATION

TDS 1A08

Ver.B/02.21

# **DRAPA RELIEF**

**Drapa Relief** is a 100% acrylic, water based decorative coating with textured finish. It is suitable for indoor and outdoor use and it can be applied on surfaces like plaster, concrete, plaster-board, hardboards etc. It does not contain ammonia and hazardous substances such as heavy metals, free formaldehyde and aromatic hydrocarbons. It has superb adhesion and excellent durability against difficult weather conditions. It has very good workability and it can give variety of final textures with the selection of the appropriate application method and tool.

## **APPLICATION**

- *Substrate Preparation*  
Surfaces must be clean, dry and free of loose materials, dusts, oils, etc. For use on old or loose concrete or plaster surfaces, it is recommended to stabilize the substrate using the **Isacryl Nerou** impregnating primer. For application on new or unpainted surfaces of concrete or plaster, prime with **Drapa Astari Plastikon** or **Isacryl Nerou** impregnating primer. Then apply **Drapa Relief** according to the desired final texture.
- *Application*  
Brush, roller. The product is ready to use.
- *Consumption*  
Approximately 1.5 kg/m<sup>2</sup>/lt depending strongly in the method of application and the final texture.
- *Drying time*  
Touch dry in 0.5 -1 hour. Recoating after 3-4 hours. The drying time depends on weather conditions (temperature, humidity).
- *Cleaning of tools*  
Try to remove as much paint as possible from the tools before cleaning them. Clean tools immediately after use with water and cleaning liquid if needed.
- *Restrictions*  
Do not apply the product when the ambient temperature and/or the substrate temperature is lower than 5°C.

## *PACKAGING*

Available in plastic pails of 5kg and 15kg.

## *STORAGE*

Store in a dry and cool place (5°C to 35°C). Keep container tightly closed.

## *SAFE USE*

Avoid contact with eyes. Consult the product's SDS for more information.

## *TECHNICAL CHARACTERISTICS*

- *Binder:* 100% Acrylic.
- *Drying:* Touch dry after 1.5hr -2hr.
- *Repainting:* After 12hr.
- *Thinning:* Ready to use. It can be thinned up to 5-10% with clean water if needed.
- *Colors:* Available in white.
- *Gloss:* Textured mat.

## *VOLATILE ORGANIC COMPOUNDS*

EU limit value for this product (cat A/c): 40 gr/lit. This product contains maximum 10 gr/lit VOC.