

TECHNICAL SPECIFICATION

TDS 1A26

Ver.B/02.21

ULTIMATE WALL ECO

Ultimate Wall Eco is an ecological, supreme quality paint for interior use certified by the Supreme Ecological Label Award Council. It has top resistance to frequent washing (Class I according to ISO13300) high whiteness and top hiding power. It does not contain ammonia or any other hazardous substance such as heavy metals, free formaldehyde, or aromatic hydrocarbons. It is ideal for application in all indoor living spaces. It has low odor and a specially designed composition that protects the user and does not burden the environment. It can be applied on plaster, concrete, bricks, plasterboards, cement boards, etc. It has excellent workability, and does not splash. Its special composition gives to it supreme levelling properties making it an ideal choice for application on surfaces that have been smoothed with putty, giving to them a beautiful mat finish. With reduced content of Volatile Organic Compounds.

APPLICATION

- **Substrate Preparation**
Surfaces must be clean, dry and free of loose materials, dusts, oils, etc. For use on old or loose concrete or plaster surfaces, it is recommended to stabilize the substrate using the **Isacryl Nerou** impregnating primer. For application on new or unpainted surfaces of concrete or plaster, prime with **Drapa Astari Plastikon** or **Isacryl Nerou** impregnating primer. Then apply two layers of **Ultimate Wall Eco**. For repainting of smooth surfaces without problematic parts, apply two hands of **Ultimate Wall Eco** directly.
- **Application**
Brush, roller or pistol, diluted 5-10% with clean water.
- **Spreading rate**
11-13 m²/lt on properly prepared surfaces.
- **Drying time**
Touch dry in 0.5 -1 hour. Recoating after 3-4 hours. The drying time depends on weather conditions (temperature, humidity).
- **Cleaning of tools**
Try to remove as much paint as possible from the tools before cleaning them. Clean tools immediately after use with water and cleaning liquid if needed.



- *Restrictions*

Do not apply the product when the ambient temperature and/or the substrate temperature is lower than 5°C.

PACKAGING

Available in plastic pails of 0.75lt, 3lt and 10lt.

STORAGE

Store in a dry and cool place (5°C to 35°C). Keep container tightly closed.

SAFE USE

Avoid contact with eyes. Consult the product's SDS for more information.

TECHNICAL CHARACTERISTICS

- *Binder:* Acrylic
- *Drying:* Touch dry after 30 min.
- *Repainting:* Minimum after 3hr.
- *Viscosity:* 6000 – 8000 cp (spindle No4, 20 rpm, 25°C).
- *Density:* 1,51-1.53 gr/ml.
- *Thinning:* 5-10% with Clean water.
- *Colors:* Available in white.
- *Gloss:* Mat.

VOLATILE ORGANIC COMPOUNDS

EU limit value for this product (cat A/a): 30 gr/lt. This product contains maximum 9 gr/lt VOC.

DRAPA
chemie

DRAPA CHEMIE - DRAKOPOYLOS S.A.
Megaridos Ave & Chiou Str, Mavri Yiora Area,
19300, Aspropyrgos, Attiki, Greece
tel: +302105570191, fax: +302105593945
Email: drapa1@otenet.gr, Url: www.drapa.gr
EN ISO 9001:2015, Cert. Nr. 123045
EN ISO 14001:2015, Cert. Nr. GR/002/2015-3

